

Technical Specification

Created by Elwin from Shenzhen ERALED Optoelectronics Co., Ltd.

Email: salesmanager9@eraled.biz ; URL: www.led-display-boards.com

◆ Technical Specification:

2.92608 by 1.09728 meters 3.2107 sqm P7.62 Indoor single color LED message display

Pixel Configuration	1R/1A	
Physical/Real pixel pitch(mm)	7.62	
Pixel density(dots/m ²)(physical/real)	17222	
Calibrated Brightness	600 nits(adjustable)	
Brightness Adjustment	100 grade auto-adjustment	
View angle(degree)(50% brightness)	Horizontal: 160° (80° off center); Vertical: 160° (80° off center)	
Interface port	DVI interface(DVI connector)	
Input signal	Video:PAL/NTSC Optioned:VGA,video,DVD,TV	
Protection grade	IP54 front side/IP54 backside	
Operating temperature(Celsius degree)	-20~+55'	
Storage temperature(Celsius degree)	-30~+55'	
Operation Humidity(RH)	0-95%	
Storage Humidity(RH)	0-99%	
Lifetime(hours)(50% brightness)	100,000 hours	
Servicing	Front and Back	
Power supply	100-240V/50-60HZ	
Screen Operation mode: scan	1/8	
LED Drive	constant-current drive	
Power consumption(W/m ²):Maximum	29	
Power consumption(W/m ²):Average	12	
Module Configuration(Pixels quantities of the module)	length	32
	height	16
Module Dimensions(mm)	length	244
	height	122
Cabinet Configuration(standard)(module quantities of the cabinet)	length	6
	height	9
Cabinet Dimensions(standard)(mm)	length	1463
	height	1097
	width	170
Screen Configuration(only eg,standard cabinet quantities of the screen)	length	2
	height	1
Screen Dimensions(m)	length	2.9261
	height	1.0973

Add:Eraled Industry Park, Xincheng Road,Shajing town,Bao an District,Shenzhen,China. [URL: www.led-display-boards.com](http://www.led-display-boards.com),
 Email:manager@eraled.biz; MSN:Eraleddisplay@hotmail.com, Skype:Eraleddisplay Tel:0086-75527592546;Fax:0086-7552759256

Screen Size(m ²)	m ²	3.2107
Recommend Optimal Viewing Distancem:minimum	Min	5
	Max	104
Physical Resolution(dots/pixels)	length	384
	height	144